



Freshwater Salt Spa Start Up

STEP 1: REMOVE PHOSPHATES FROM WATER

- Add 1 Bottle of Fresh Start Plus
 - After 24 hours, remove and rinse filters

STEP 2: LOWER CALCIUM LEVEL IN SPA

- Rinse the Vanishing Act Pillow and place in footwell of spa
 - After 12 hours flip pillow and reposition in footwell

SPA	SALT (CUPS)	OUTPUT LEVEL
SX, TX	4 ½	LEVEL 4
JETSETTER, JETSETTER LX, STRIDE	5	LEVEL 5
PRODIGY, SOVEREIGN, BEAM, PACE	6	LEVEL 5
ARIA, TRIUMPH, VANGUARD, FLAIR, FLASH, RELAY, RYTHM	7 ½	LEVEL 5
GRANDEE, ENVOY, PULSE	10¼	LEVEL 6
PRISM	12	LEVEL 7

STEP 3: ACTIVATE YOUR SALT SYSTEM

- Add recommended amount of salt, shown on table, with jets running allow 5 minutes for salt to dissolve
- Set your spa's output level shown on table
- Add 1 capful of Simple Blue Power Boost
- Wait 5 minutes before proceeding to Step 4

STEP 4: ESTABLISH THE CHLORINE RESIDUAL

- Test your water
 - If the chlorine is **below** 3ppm, add 1 more capfuls of Power Boost
 - After 24 hours, test your water. Repeat Step 4's process until you achieve 3ppm of chlorine

NOTE: It can take a few to days to build a chlorine residual based on your initial hot tub usage and fill water quality

ROUTINE MAINTENANCE:

10 Day Maintenance Reminder

- **(Highlife/Limelight) Logo light flashing**
- **(Hotspot) Topside indicator power/ready flashing**
 - To turn this reminder off, you must confirm the output in the water care menu.
 - Test spa water and balance according to the ranges shown below
 - If chlorine is high, reduce the output level (1 increment at a time). **Wait 24 hours, if chlorine level is still high, call store or bring in a water sample for advice.**
 - If chlorine is low, raise the output level (1 increment at a time) and add 1 capful of Power Boost. **Wait 24 hours and retest. If chlorine level is still low, add 1 cap of Power Boost and repeat as needed.**
- **MONTHLY:**
 - Clean filters thoroughly
- **EVERY 4 MONTHS:**
 - System will prompt you to replace the Freshwater Salt Cartridge. Follow instructions on control panel in salt system menu.
- **EVERY WATER CHANGE:**
 - Before changing water, remove filters and chemically clean with Simple Blue FC-5 Filter Cleaner to remove body oils and minerals that rinsing alone will not remove. Put filters back in and run spa. This is done to prevent foaming of new water.
 - Clean spa cover and protect it with 303 Cover Protectant

Water Test Parameters	OK Range	
	Minimum	Maximum
Salt	1,500 ppm	2,000 ppm
Hardness	25 ppm	75 ppm
Alkalinity	40 ppm	120 ppm
pH	7.2	7.8
Chlorine	1 ppm	5 ppm